



ADA124415




COMPUTER SCIENCE  
TECHNICAL REPORT SERIES



UNIVERSITY OF MARYLAND  
COLLEGE PARK, MARYLAND

20742

DTIC FILE COPY



02 02 11 041

TR-1025 0138  
DAAG-53-76C-1038

March 1981

## MULTIBAND PYRAMID LINKING

Tsai-Hong Hong  
Azriel Rosenfeld

Computer Vision Laboratory  
Computer Science Center  
University of Maryland  
College Park, MD 20742

### ABSTRACT

A method of image segmentation has been developed based on creating links between pixels in successive layers of a "pyramid" of reduced-resolution versions of the image. In the original implementation of this method, the links were based on comparing the values of a single feature, (average) gray level, for each pixel. In this note, the method is extended to links based on multiple features, such as color components or neighborhood properties.

DTIC  
SELECTE  
FEB 16 1981  
H


#### DISTRIBUTION STATEMENT A

Approved for public release;  
Distribution Unlimited

The support of the Defense Advanced Research Projects Agency and the U.S. Army Night Vision Laboratory under Contract DAAG-53-76C-0138 (DARPA Order 3206) is gratefully acknowledged, as is the help of Sherry Palmer in preparing this report.

A method of image segmentation described in [1] is based on creating links between pixels in successive layers of a "pyramid" of reduced-resolution versions of the image. The method makes use of an "overlapped" pyramid in which each level is initially obtained by averaging 4-by-4 blocks of pixels on the level below, where these blocks overlap by 50% in the x and y directions; this implies that each pixel has four "fathers" on the level above it. To segment the image, we link each pixel (at each level of the pyramid) to that one of its four fathers whose gray level is most similar to its own. We now recompute the value of each pixel (on the levels above the image itself) by averaging only those pixels on the level below that are linked to it. Based on these new values, we change the links as necessary; recompute the values based on these new links; and so on, repeating the process until there is no further change (typically after a few iterations). The resulting final links define subtrees of the pyramid, having pixels as leaves and having roots at the uppermost level, which we usually take to be the 2-by-2 level. Each subtree thus defines a subset of the pixels (its leaves), so that we have segmented the image into (at most) four subsets.

The linking process need not be used on average gray level;; we can use any property that can be computed for the pixels of the image, and extend this property to the higher





levels of the pyramid by averaging. If desired, we can begin the process by dividing the image into blocks, computing a property (e.g., a textural property) for each block, and building a pyramid starting from the resulting array of property values; linking in this pyramid yields a (blocky) segmentation of the image into (at most four) textured regions [2]. Other modifications of the basic pyramid linking process have been investigated, including the use of weighted rather than forced-choice links [3], as well as variations of the linking criterion that take positional information into account [4]. Methods of combining this linking scheme with image segmentation by recursive splitting into homogeneous regions have also been investigated [5].

The linking process need not be based on a single property; we can compute a property vector for each pixel (or block) and extend it to the higher levels of the pyramid by componentwise averaging. This note illustrates this generalization with some simple examples of pyramid linking based on pairs of properties.

Figure 1a shows the red, green, and blue bands of a color image of part of a house, showing sunlit and shadowed brick, bushes, and grass. Figure 1b shows the results of the pyramid linking process applied to each band separately; the pixels belonging to each of the four subtrees are displayed with a

yields the four types of regions, but the results in the green band yield the brick (both sunlit and shadowed) as essentially a single region, while dividing the bushes into two classes. All results shown are for ten iterations.

Working with two features does not always yield significant improvement over working with single features. Table 1 shows classification results for two geological terrain types, Lower Pennsylvanian Shale and Pennsylvanian Sandstone and Shale, using three texture features, singly and pairwise. Each feature was the moment of inertia of a gray level co-occurrence matrix about its main diagonal (Haralick's "CON" feature), where the matrices were defined for the displacements shown in the second column of the table. In earlier texture classification studies using the same terrain types [6], these features individually had error rates of close to 25%, whereas pairwise they gave error rates of under 10%. In the present experiment, however, there is little or no improvement when pairs are used, probably because the error rates for single features are so low.

In conclusion, these examples illustrate how the basic pyramid linking method may sometimes yield a richer class of segmentations by using more than one property to

characterize the pixels. Pyramid linking appears to deserve further investigation as a general approach to image segmentation.

## References

1. P. Burt, T.H. Hong, and A. Rosenfeld, Segmentation and estimation of image region properties through cooperative hierarchical computation, TR-927, Computer Vision Laboratory, Computer Science Center, University of Maryland, College Park, MD, August 1980.
2. M. Pietikäinen and A. Rosenfeld, Image segmentation by texture using pyramid node linking, TR-1008, Computer Vision Laboratory, Computer Science Center, University of Maryland, College Park, MD, February 1981.
3. K.A. Narayanan, S. Peleg, A. Rosenfeld, and T. Silberberg, Iterative image smoothing and segmentation by weighted pyramid linking, TR-989, Computer Vision Laboratory, Computer Science Center, University of Maryland, College Park, MD, December 1980.
4. T. Silberberg, S. Peleg, and A. Rosenfeld, Multi-resolution pixel linking for image smoothing and segmentation, TR-977, Computer Vision Laboratory, Computer Science Center, University of Maryland, College Park, MD, November 1980.
5. M. Pietikäinen, A. Rosenfeld, and I. Walter, Split-and-link algorithms for image segmentation, TR-1026, Computer Vision Laboratory, Computer Science Center, University of Maryland, College Park, MD, March 1981.
6. J.S. Weszka, C.R. Dyer, and A. Rosenfeld, A comparative study of texture features for terrain classifications, IEEE Trans. SMC-6, 1976, 269-285.

<u>Feature No.</u>	<u>Displacement</u>	<u>Error rate(%)</u>	<u>Feature pair</u>	<u>Error rate(%)</u>
1	(1,0)	4.3	2&3	3.3
2	(0,1)	6.4	3&1	5.2
3	(0,2)	14.2	1&2	6.2

Table 1. Classification results for geological terrain types



(a)



(b)




(c)




Figure 1. a) House image: red, green and blue components  
b) Results of pyramid linking applied to each band separately  
c) Results using pairs of bands: green/blue, blue/red, red/green

(a)



(b)



(c)



Figure 2. a) "Busyness" values in the three bands  
b) Results of pyramid linking applied to these values  
c) Results using (intensity, busyness) feature pair in each band

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
	AD-A124415	
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED
MULTIBAND PYRAMID LINKING		Technical
		6. PERFORMING ORG. REPORT NUMBER
		TR-1025
7. AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(s)
Tsai-Hong Hong Azriel Rosenfeld		DAAG-53-76C-0138
9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Computer Science Center University of Maryland College Park, MD 20742		
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
U.S. Army Night Vision Laboratory Fort Belvoir, VA 22060		March 1981
		13. NUMBER OF PAGES
		7
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)		
Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
Image processing                      Texture Pattern recognition Segmentation Pyramids Color		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)		
A method of image segmentation has been developed based on creating links between pixel in successive layers of a pyramid of reduced-resolution versions of the image. In the original implementation of this method, the links were based on comparing the values of a single feature, (average) gray level, for each pixel. In this note, the method is extended to links based on multiple features, such as color components or neighborhood properties.		